

# TAMKO® SLATE SURFACE

## ROLL ROOFING

MANUFACTURED IN JOPLIN, MO AND GREEN COVE SPRINGS, FL

## PRODUCT DATA

### DESCRIPTION

Information included in this product data sheet was current at time of printing.

To obtain a copy of the most current version of this product data sheet, visit us online at [tamko.com](http://tamko.com) or call us at 800-641-4691.

**TAMKO® SLATE SURFACE ROLL ROOFING** is constructed from TAMKO's organic mat, impregnated with hot asphaltic saturant, then coated on both sides with weathering grade asphalt and surfaced with mineral granules.

**USES:** For application to roof decks with inclines of not less than 2 inches per foot.

**NOTICE: THIS PRODUCT IS SOLD "AS IS" AND WITHOUT WARRANTY OF ANY KIND. ALL WARRANTIES, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE EXCLUDED.**

### COLORS

- Empire Green Blend\*
- Rustic Black
- Rustic Cedar
- Weathered Wood\*
- White

\*Manufactured by Joplin

### PRODUCT DATA

Roll Size†	36" × 36'
Roll Contains	1.08 Squares
Coverage per Roll††	1.02 Squares

†Subject to manufacturing variation

††When applied according to application instructions



P.O. Box 97  
Galena, KS 66739-0097  
800-641-4691  
[tamko.com](http://tamko.com)

**WARNING:** This product contains crystalline silica and wood dust. Crystalline silica and wood dust have been classified as "known human carcinogens" by the International Agency for Research on Cancer (IARC) and the National Toxicology Program. This product also contains oxidized asphalt. Occupational exposures to oxidized asphalt and its emissions during roofing have been classified by IARC as a "probable human carcinogen". Oxidized asphalt also contains Polycyclic Aromatic Hydrocarbons some of which have been classified by IARC as "known" or "probable human carcinogens". The physical nature of this product may help limit any inhalation or dermal hazard during application and/or removal. However, physical forces such as sawing, grinding or drilling during demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. Take precautions to prevent breathing and contact with skin.



**IMPORTANT SAFETY INFORMATION:** Do not install until all appropriate safety precautions have been read and understood. The TAMKO Safety Data Sheet (SDS) is available at [tamko.com/sds](http://tamko.com/sds). Always use appropriate fall protection equipment and wear appropriate personal protective equipment (PPE) when working with this product. Moisture, frost, debris or other material will decrease the traction and can cause slippery conditions when walking on the product. **Applicator safety is of utmost importance.**