

# TAMKO® TWM-1 MASTIC

## RUBBERIZED BITUMEN MASTIC

MANUFACTURED FOR COLUMBUS, KS

## PRODUCT DATA

### DESCRIPTION

Information included in this product data sheet was current at time of printing.

To obtain a copy of the most current version of this product data sheet, visit us online at [tamko.com](http://tamko.com) or call us at 800-641-4691.

**TWM-1 MASTIC** is a high quality, trowel grade, rubberized bitumen mastic. TWM-1 dries to a pliable seal allowing for minor expansion and contraction.

- Available in 3 gallon buckets
- Applied with a trowel
- 5-Year Limited Warranty and Arbitration Agreement

**USES:** For multiple uses, including finishing the edge of seams, overlaps, patches and terminations of properly sealed TAMKO waterproofing membranes. This product is also suitable for use in roof flashing application and contains additives for use in wet and dry conditions.

**WATERPROOFING PRODUCTS BEGIN TO AGE AS SOON AS THEY ARE EXPOSED TO NATURE. BUILDINGS EXPERIENCE AGING FACTORS DIFFERENTLY, SO IT IS DIFFICULT TO PREDICT HOW LONG WATERPROOFING PRODUCTS WILL LAST. TAMKO PROVIDES A LIMITED WARRANTY FOR MANY PRODUCTS, THAT INCLUDES A BINDING ARBITRATION CLAUSE AND OTHER TERMS AND CONDITIONS WHICH ARE INCORPORATED HEREIN BY REFERENCE. YOU MAY OBTAIN A COPY OF THE LIMITED WARRANTY AT TAMKO.COM OR BY CALLING 1-800-641-4691.**

### APPLICATION

Apply with a trowel. Apply with a trowel to a 1/8" thickness and a width of 1/2" to 1" and worked into all terminations.

### COVERAGE RATES

Side Laps: 900 lineal feet per gallon

End Laps: 600 lineal feet per gallon

### LIMITATIONS

- Not suitable for use as a waterproofing concrete/masonry sealer.
- When used to terminate the edges of a TAMKO Waterproofing membrane, the use of TWM-1 Mastic is not a substitute for the seal of the waterproofing membrane itself.

### TYPICAL PHYSICAL PROPERTIES

Color	Black
VOC on SDS:	<250 g/l estimated
Flash point on SDS:	100.0° - 140.0°F Cleveland Open Cup
Packaging	3 gallon pails



**WARNING:** This product contains crystalline silica. Crystalline silica have been classified as "known human carcinogen" by the International Agency for Research on Cancer (IARC) and the National Toxicology Program. This product contains asphalt. The National Institute for Occupational Safety and Health has concluded that the fumes of heated roofing asphalt are a potential occupational carcinogen. The physical nature of this product may help limit any inhalation or dermal hazard during application and/or removal. However, physical forces such as sawing, grinding or drilling during demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. Take precautions to prevent breathing and contact with skin.

P.O. Box 97  
Galena, KS 66739-0097  
800-641-4691  
[tamko.com](http://tamko.com)