

ENVISION PVC™
DECKING **TAMKO®**

Redefining deck performance and durability.



Introducing Envision PVC™ decking by TAMKO®, offering all the low maintenance durability of PVC decking materials— as well as additional performance attributes that make it even easier to appreciate. Envision PVC decking contains no fillers such as plant fibers, wood or sawdust, providing consistent density throughout and moisture resistance. It also features a special formulation to assure long-lasting colors! And with its striking realistic wood grain finish² and grooved board for hidden fastener installation, it creates a distinctively beautiful extension to your home.

Simply stunning performance—including excellent scratch and stain resistance.

- Envision PVC™ decking is manufactured with advanced cellular vinyl technology for an extremely hard surface that provides performance and durability
- Provides excellent resistance to staining, scratching and splitting
- 25-year limited warranty³ against rotting, cracking, delaminating and termite damage
- Offers low maintenance—cleans with an occasional washing of mild soap and water
- Ideal for pools and marinas
- Class A rating E-84 for flame spread

Envision PVC is designed to last.

No Organic Fibers

- Manufactured with absolutely no organic fillers, to create a solid core PVC material
- Solid core monoextrusion process provides consistent density throughout—there's nothing to come apart or delaminate

Special Formulation

- Surface is infused with unique pigments for UV protection and long-lasting colors¹
- Surface formulation also helps to provide excellent resistance to weathering and fading¹
- Heat-reflective characteristics enable the deck to stay cooler to the touch of your feet (when compared to a wood deck)

Impressive Beauty

- Wood grain texture creates striking natural beauty²
- Available in three attractive colors: Grey, Sand and Taupe¹

Intelligent Design

- Grooved boards allow installation with hidden fasteners, creating a stunningly smooth and sleek look
- Thick 5/8-inch finished edge skirting helps guard against warping issues
- 20-foot solid boards without grooves are available to finish the look

Affordability

- Compare to other PVC decking products and see for yourself

As easy to install as it is to enjoy.

Envision PVC decking installs with the same tools used for most deck installations³

- Light in weight/easy to handle and cut
- No need to predrill for fasteners, saving time and labor
- Available in 12-, 16- and 20-foot board lengths; skirting board length is 12 feet
- Hidden fastener installation is easy; boards can also be installed with stainless steel deck screws³
- Screws can be countersunk close to the board ends without splitting the deck material when applied in accordance with TAMKO® written installation instructions³

Choose an equally durable railing system.



As a patented triple-layer railing system, the Tam-Rail® system by TAMKO adds incredible strength, protection and durability. It's the ideal complement to your Envision PVC deck.

¹Representation of these colors is as accurate as our printing will permit. View several full-length pieces of material prior to final color selection and installation. Color of material could weather to a lighter shade.

²View a full-length board to fully appreciate the wood grain pattern of Envision PVC decking.

³To obtain a copy of the limited warranty, the most current version of this sales sheet or the product installation instructions, visit tamko.com or call 1-800-641-4691. Information included in this sales sheet was current at the time of printing.

©2009 TAMKO Building Products, Inc. TAMKO and Tam-Rail are registered trademarks and Envision PVC is a trademark of TAMKO Building Products, Inc.
U.S. Patent Nos. 6,827,995 and D461,914




TAMKO Building Products, Inc.
P.O. Box 1404 • Joplin, MO 64802
1-800-641-4691



Choose from three attractive color options.



Taupe



Sand



Grey

Decking Profiles

Nominal Size	Actual Size
1"x6" x (12', 16' or 20')	1" x 5 1/2"
Finished Edge Skirting (12')	5/8" x 11 1/4"

Solid boards without grooves available in 20-foot lengths only.
All tolerances +/- 1/16"

Span Chart

*Maximum recommended center-to-center spans with a minimum of three joists

	Residential Decks & Light-Duty Decks	Commercial Decks, Boardwalks & Marinas
Live Load	100psf	100psf
1"x6"	16"	16"

*NOTE: When a 45° diagonal installation is used, subtract 4" in the maximum span. Envision PVC decking products are nonstructural products. These decking products should not be used in a structural manner, including use as joists, load-bearing columns, stringers or beams.

TAMKO
BUILDING PRODUCTS
tamko.com